

eBridge100ST

IP and PoE/PoE+ over Coax Hardened Mini Transceiver

Description

Altronix eBridge100ST EoC hardened transceiver transmits data at 100Mbps, Full Duplex over Coax cable to a paired eBridge receiver and provides power in a PoE/PoE+ compliant format to an enabled device/camera. The eBridge receiver is available in various options and is powered by an external midspan or endspan. The receiver passes PoE/PoE+ power over the same coax cable to the eBridge100ST transceiver which, in turn, passes this power to an enabled IP camera/device. These plug and play units facilitate a cost-effective, simple way to replace legacy analog products with new IP devices over existing coax up to 300m.



eBridge100ST

Key Features

- IEEE 802.3af (15W) and IEEE 802.3at (30W) compliant.
- Throughput is rated to pass 100Mbps at distances up to 300m.
- Eliminates the costs and labor associated with installing new network cabling.
- Retrofit digital IP cameras in an analog CCTV installation.
- Auto detection and protection of legacy non-PoE cameras/devices.
- Works with Megapixel, HD720, HD1080 & VGA (SD) cameras.
- Extends Network link distance in an industrial environment.
- Upgrades deployed CCTV Coax to a digital network for Retail, Casinos, Airports, Schools, Hospitals, etc.
- UL Listed in the U.S. and Canada.
- CE Approved.
- Lifetime Warranty / Made in the U.S.A.

Compatible Receivers:



eBridgePlus Receivers:

eBridge100RM - Single Port EoC Receiver
 eBridge400PCRM - Four (4) Port EoC Receiver
 eBridge800PCRM - Eight (8) Port EoC Receiver
 eBridge1600PCRM - Sixteen (16) Port EoC Receiver
 Transmit IP video/data over coax up to 300m @ 100Mbps.
 Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).
 UL/cUL Listed (UL60950-1). CE and C-Tick Approved.



eBridge800E - Eight (8) Port EoC Receiver with Integral PoE+ Switch
 Provides 30W full power per port (240W max) over coax up to 300m @ 100Mbps.
 Supports PoE (IEEE 802.3af) and PoE+ (IEEE 802.3at).
 CE Approved.

eBridge100ST

IP and PoE/PoE+ over Coax

Hardened Mini Transceiver

Specifications

Input

Operating power provided by eBridge receiver.
Power consumption: 1.5W.

Coax

Throughput rated at 100Mbps at distances up to 300m.
Speed: 10/100BaseT, half/full duplex, auto negotiation.
Connectivity: BNC, RG-59/U or similar.

Indicators (LED)

Blue LED: Coax link connection.
Green LED: PoE ON.
Yellow and Green LED (by RJ45 jack):
IP Link status, 10/100Base-T/active.

Agency Listings

UL/cUL	UL 60950-1 (Information Technology Equipment).
CE	European Conformity.

Physical and Environmental

Dimensions (W x L x H)

2.27" x 2.645" x 1.12" (57.7mm x 67.2mm x 28.4mm).

Weight (approx.)

Product Weight	0.22 lbs. (0.1 kg).
Shipping Weight	0.4 lbs. (0.18 kg).

Temperature

Operating	
For 15W:	-40°C to 75°C (-40°F to 167°F).
For 30W:	-40°C to 60°C (-40°F to 140°F).

Storage	-40°C to 75°C (-40° to 167°F).
---------	--------------------------------

Relative Humidity	85% +/-5%.
-------------------	------------

Operating Altitude:	-304.8 to 2,000m.
---------------------	-------------------