

Resolution Compatibles

UNIVERSAL TRANSLATOR: RE508X RE524X

Simple, Comprehensive, Robust

The Universal Translator family delivers on all of your account take-over needs, while minimizing your inventory challenges. With only two part numbers, your technicians will be equipped to get the job done on any install. The wireless model can even be utilized as a repeater, helping minimize service calls due to supervisory issues. We invented the Translator product category, and we listened to our customers. The Universal Translator was designed for you.



RE508X Hardwire-to-Wireless Translator



RE524X Wireless-to-Wireless Translator

- Fast and easy installation without any exposed antennas.
- Rechargeable battery.
- Spacious and well-designed wiring areas to ensure quality, error free installations.
- Single button, simplified enrollment reducing learning curves and programming errors.
- Field configurable RF settings handling all widely installed sensors and panels on the market
- Hardened design enabling UL compliance*
- Wireless models can be field configured to act as a repeater extending sensor coverage when needed.

*UL standard compliance certified by ETL: pending



RE508X HARDWIRE-TO-WIRELESS TRANSLATOR SPECIFICATIONS

- **Input:**
8Zones
- **EOL Resistor:**
Any or none
- **Output:**
GE®, Honeywell®, 2GIG™, CryptiX™, and DSC™
- **Coverage:**
Dual Diversity antennas for whole house coverage
- **Regulatory:**
UL1023 Compliance*
- **Power Supply:**
No need to use an external power supply or a supply from the existing panel
Backup battery comes connected and activates on first power-up
Simple barrel power connector
Loss of wall power warning chirp
Wall power supply included
- **Backup:**
24 hour backup all contact zones
Powered devices: 200mA max, 4 hours battery backup @ 80mA
- **Tamper:**
Cover Tamper capable
- **Automation:**
Automatic detection of sensor type to reduce programming complexity
- **Programming LOCK:**
Prevents competing dealers from taking over the Translator

*UL standard compliance certified by ETL: pending



RE524X WIRELESS-TO-WIRELESS TRANSLATOR SPECIFICATIONS

- **Input:**
64 Zones Translation for Honeywell. Unlimited for others. GE, Napco™, Honeywell, 2GIG, and DSC
- **Output:**
GE, Honeywell, 2GIG, and DSC
- **Repeater:**
GE, Honeywell, 2GIG, and DSC
- **Coverage:**
Dual Diversity antennas for whole house coverage
- **Regulatory:**
UL1023 Compliance*
- **Power Supply:**
No need to use an external power supply or a supply from the existing panel
Backup battery comes connected and activates on first power-up
Simple barrel power connector
Loss of wall power warning chirp
Wall power supply included
- **Backup:**
24 hour backup all zones
Powered devices: 200mA max, 4 hours battery backup @ 80mA
- **Tamper:**
Cover Tamper capable
- **Automation:**
Automatic detection of sensor type to reduce programming complexity
- **Programming LOCK:**
Prevents competing dealers from taking over the Translator