
Slim Line II Wi-Fi Doorbell Camera (ADC-VDB105x/106x) - Data Sheet

Overview

The Slim Line II Wi-Fi Doorbell Camera makes it easy to deliver front door awareness to even more customers! The Slim Line II delivers an engaging customer experience with Two-Way Audio, live and recorded video, and notifications. The Slim Line II has an integrated camera, PIR motion sensor, and digital microphone and speaker, that enables homeowners to answer the door and speak right from their app. Customers can also record doorbell triggered clips, set motion triggered automation rules, and receive realtime alerts.

Features

- 720p live video
- Doorbell with integrated camera
- PIR-triggered motion sensitivity (low, medium, and high settings)
- Digital microphone and speaker
- Doorbell-triggered clips
- Motion-triggered automation rules
- Real-time alerts
- Battery heater for improved cold weather performance

Included accessories

- Wall mounting bracket
- Wall screws
- Masonry anchors





Specifications

Power	<p>Operational range is 10-30 VAC, 10 VA or 12 VDC 0.5 to 1.0 A wired to an in-home mechanical or digital doorbell chime. Digital doorbell chime compatibility requires SkyBell Digital Doorbell Adapter - not included.</p> <p>Alarm.com recommends a minimum of 12 VAC for consistent functionality, but the recommended range for best results is 16-24 VAC.</p>
Wi-Fi	Compatible with Wi-Fi 802.11 b/g/n/ ac, 2.4 and 5 GHz
Minimum Bandwidth Requirement	2 Mbps
Video Camera	1.3 MP, full-color
Lens / angle of view	170° horizontal, 110° vertical
Resolution	Live: 720p (adjustable to lower resolution if required) Recorded: 720p
Night vision	Infrared
Microphone	Omni-directional
Motion Sensor	Detects motion up to 8 ft range
Dimensions (width x depth x weight)	1.4 x 4.8 x 1.1" (3.65 x 12.2 x 2.86 cm); 3.1 oz (87.9 g)
Weather Rating	IPX4 rated
Operating Temperature	-40°F to 122°F (-40°C to 50°C)
Operating Humidity	Operating Humidity (RH): 10% to 80%

