



2-7001

Description

Suttle SpeedStar™ Category 5e modular jacks exceed TIA/EIA-568-C.2 specifications for Category 5e component performance.

SpeedStar™ modules are for use with Suttle's SpeedStar™ faceplates, bezels and surface mount housings. Termination requires use of a punch down installation tool.

Available in a white housing, each jack comes with multi-color bezels for your installation.

Product Specifications

Wiring:	568A or 568B
Insertion Life:	750 insertions
Housing:	High impact, UL 94V-0 rated thermoplastic
Contacts:	50 microinch hard gold plating minimum with 100 microinch nickel

Features

- Easy installation from rear of faceplate
- Compatible with SpeedStar™ products (bezels, faceplates, and surface mount housings)
- Terminates with standard 110 termination tools
- Dust covers for IDC terminations

Electrical Specifications

Contact Pressure:	>100 grams
Contact Resistance:	<10 milliohms
Insulation Resistance:	>500 megohms
Current/Voltage:	140 VDC @ 1.5 amps (2-7001) 140 VDC @ 2 amps (STAR600A&B)
Dielectric Withstand:	1000 VAC RMS @ 60Hz



Product Information

Suttle

Part Number	Description
-------------	-------------

2-7001	8-Position, 8-Conductor Jack, 568A/B, 110 IDC Block
<i>Bezel Colors (-xx): (-51) Green, (-52) Electrical Ivory, (-53) Red, (-56) Yellow, (-62) Blue, (-64) Lt. Almond, (-85) White, (-97) Orange</i>	