Complete Fire Panel Protection for Signaling and Notification





Product Features

IK-TSS3

- Hard-wired base for 2MHLP/2MHTP modules, protects up to 4 SLC, NAC, IDC, PIV and dialer circuits pairs (modules sold separately)
- Complete protection, simple installation, high quality, and field-replaceable modules make the TSS3 a perfect fit for alarm systems or control panels.

Applications

- Fire Alarm Panels
- Control Panels
- UL Listed Control Panels where a UL Recognized Component is Required

Accessories

Test Module Kit – Part Number DTK-2MHLPTM

Example to protect two 24V data/signal pairs and two telco pairs: **1 x DTK-TSS3** (DTK-2MB in NEMA enclosure)

- 1 x DTK-2MHLP24B (protect 2-data/signal pairs 24V)
- 1 x DTK-2MHTP (protect 2-telco pairs)

DITEK's Total Surge Solution (TSS) is a range of products that provide total surge protection for addressable and conventional alarm systems.

The DTK-TSS3 is a perfect fit for building to building notifier and communication runs. It comes with a prewired four-pair mounting base. Adding DTK-2MHLP/2MHTP modules for data/signal and dialer circuit protection provides a complete solution for your fire alarm system.

Technical Specifications	
Multi-base system, 4 circuit pairs See DTK-2MHLP Datasheet for detailed information	

Mechanical Characteristics

Polycarbonate NEMA 4X (IP66)
UL Listed Industrial Control Panel Enclosure
UL94 Flammability Rating
-40°F - 175°F (-40°C - 80°C)
95% non-condensing
7"L x 4"W x 4"H
(178mm x 102mm x 102mm)
4 lb. (1.8kg)

Quality, Standards & Approval

Agency Approvals:	UL497B for DTK-2MHLP UL497A for DTK-2MHTP
Standards Compliance:	IEEE C62.41.1 –2, IEEE C62.45
Warranty:	Ten Year Limited Warranty

Every precaution has been taken to ensure that this literature is accurate and complete. DITEK Corporation assumes no responsibility and disclaims all liability for damages resulting from the use of this information or for any errors or omissions.

