# HES<sup>®</sup> 8500 Electric Strike

## **ASSA ABLOY**

The global leader in door opening solutions



# The fire-rated, concealed electric strike solution for mortise locksets.

## Saves Time

- No cutting into the face of the frame
- Maintains the guidelines for retrofit into fire-rated frames
- Manages a deadlatch in almost any position


## **Superior Aesthetics**

- Completely concealed and requires no cutting on the face of the frame
- Available in today's most popular finishes
- Fits in standard ANSI prep

## Quality and Safety


- UL 10C fire-rated, keeping the door securely closed for three hours in fail secure mode
- ANSI/BHMA A156.31, Grade 1
- UL 1034, burglary-resistant listed and suitable for outdoor use





## No Cutting | Fire-Rated | Mortise Latchbolts

## Dimensions



#### 10 1-7/8' [48mm] 1-7/16" [37m] T

Removal of the dustbox required for use with ANSI/BHMA A156.115 prep

## How to Order

Series	Finish*	Option (s)
8500	- 630	– LBM
<b>8500</b> Universal Electric Strike; Faceplates ordered separately	605 Bright Brass	LBM Latchbolt Monitor
	606 Satin Brass	LBSM Latchbolt Strike Monitor
	612 Satin Bronze	
	613 Bronze Toned	
	629 Bright Stainless Steel	
	630 Satin Stainless Steel	
	<b>BLK</b> Black	
*Complete Pacs are only available in the 630 finish		

## Specifications

#### Certifications

- ANSI/BHMA A156.31, Grade 1
- UL 1034 burglary-resistant listed and suitable for outdoor use
- UL 294 listed
- **RoHS** compliant
- UL 10C fire-rated, 3 hour single door (fail secure only)
- CAN/ULC-S104 fire door conformant
- NFPA-252 fire door compliant
  - ASTM-E152 fire door compliant
  - NFPA 80-07 compliant

#### Frame Application

- Metal
- Wood

## Electrical (DC Continuous Duty)

- Dual voltage 12/24 VDC/VAC
- 240 mA at 12 VDC/120 mA at 24 VDC
- PoE friendly

## Features

### Standard Features

- No cutting to the face of the frame
- Stainless steel construction
- Tamper-resistant
- Static strength 1,500 lbs
- Dynamic strength 70 ft-lbs

#### Endurance 1 million cycles

- Field selectable fail secure/ fail safe
- Non-handed
- Metal or wood frame
- Internally mounted solenoid
- Accommodates 3/4" mortise latchbolts
- Strike body depth 1-5/16"
- Plug-in connector
- Full pocket shims for horizontal adjustment
- SecuriCare five-year, no-fault, no questions asked warranty

## **Optional Features**

- LBM Latchbolt monitor •
- LBSM Latchbolt strike monitor
- 4 faceplate option kits to work with most mortise locksets

#### Accessories

- 2001M Plug-in bridge rectifier
- 2004M ElectroLynx® adapter
- 2005M3 SMART Pac® III
- 2006M Plug-in buzzer •
- 150 Strike latch guard

🧈 800.626.7590 \mid 🖵 assaabloyesh.com 📔 🗠 customerservice.esh@assaabloy.com

Copyright © 2018, Hanchett Entry Systems, Inc., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Hanchett Entry Systems, Inc. is prohibited. ESH-HES-27-0818