

**Overview**

- This unit converts a 115VAC 60Hz input, to 12VDC @ 4 amp or 24VDC @ 3 amp of continuous supply current Class 2 Rated power limited output.

Specifications

- 12VDC or 24VDC selectable output.
- 12VDC @ 4 amp or 24VDC @ 3 amp supply current.
- Class 2 Rated power limited output.
- Input 115VAC / 60Hz, 1.45 amp.
- Input fuse rated @ 3.5 amp/250V.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.
- Built-in charger for sealed lead acid or gel type batteries.
- Maximum charge current .7 amp.
- Automatic switch over to stand-by battery when AC fails (zero voltage drop).
- AC fail supervision (form "C" contacts).
- Low battery supervision (form "C" contacts).
- Battery presence supervision (form "C" contacts).
- AC input and DC output LED indicators.
- Enclosure:
 - Combination knockouts are 1/2" and 3/4"
- Product weight: 10.2 lbs.
- Shipping weight: 10.9 lbs.

Agency Approvals

- UL 294 UL Listed for Access Control System Units.
- UL 603 UL Listed Standard for Power Supplies for Use with Burglar-Alarm Systems.
- UL 1069 UL Listed Hospital Signaling and Nurse Call Equipment.
- UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.



Approved

MEA - NYC Department of Buildings Approved.



CSFM - California State Fire Marshal Approved.

Enclosure Dimensions

12.25"H x 7.75"W x 4.5"D

