

DS-2CC52D9T-AITZE

2 MP Indoor Ultra-Low Light PoC Dome Camera



- 2 MP High Performance CMOS
- Analog HD Output, up to 1080p Resolution
- Ultra-Low Light Pro
- Auto Focus, 2.8 mm to 12 mm Motorized Vari-Focal Lens
- 120dB True WDR, 3D DNR
- EXIR 2.0 with up to 130 ft (40 m) IR Range
- Dual Output: 1 HD Analog Output and 1 CVBS Output
- PoC.at, Smart Voltage Detection
- 1 Alarm Input and Output
- Up-the-Coax (HIKVISION-C)

The Hikvision DS-2CC52D9T-AITZE 2 MP Indoor Ultra-Low Light Power-over-Coax (PoC) Dome Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR is Hikvision's proprietary IR extended range technology, which has a range of 130 feet (40 meters).

The 2.8 mm to 12 mm lens is optimized for viewing angles that fit any situation. True 120 db WDR (Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

Available models:
DS-2CC52D9T-AITZE



Specifications

DS-2CE56D8T-AITZ

Camera

| | |
|--------------------------|---|
| Image Sensor | 2.0 MP progressive scan CMOS |
| Signal System | PAL/NTSC |
| Effective Resolution | 1920 (H) × 1080 (V) |
| Frame Rate | PAL: 1080p @ 25 fps, NTSC: 1080p @ 30 fps |
| Minimum Illumination | 0.003 lux @ (F1.2, AGC ON), 0 lux with IR |
| Shutter Time | PAL: 1/25 s to 1/50,000 s, NTSC: 1/30 s to 1/50,000 s |
| Slow Shutter | Maximum: 30 times |
| Lens | 2.8 mm to 12 mm |
| Horizontal Field of View | 32.1° to 98° |
| Lens Mount | Ø14 |
| Auto Iris | Supported |
| Day & Night | IR cut filter |
| Angle Adjustment | Pan: 0° to 340°, tilt: 0° to 75°, rotate: 0° to 355° |
| Synchronization | Internal synchronization |
| WDR | > 120 dB |

Menu

| | |
|------------------------|--|
| AGC | Supported |
| Day/Night Mode | Auto/Color/BW (Black and White) |
| White Balance | ATW/AWC-SET/MANUAL |
| Privacy Mask | ON/OFF, 8 programmable privacy masks |
| Motion Detection | 4 programmable motion areas |
| Backlight Compensation | WDR/BLC/HLC/OFF |
| 2D and 3D DNR | ON/OFF |
| Voltage Detection | Supported |
| Scene | Indoor/outdoor/indoor/low light |
| Functions | Defog, mirror, defective pixel correction, sharpness, camera title |





Interface

| | |
|--------------|--------------------|
| Video Output | 1 HD analog output |
| Alarm | 1 alarm in and out |

General

| | |
|----------------------|--|
| Operating Conditions | -40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation) |
| Power Supply | 24 VAC/12 VDC ±30%/PoC.at |
| Power Consumption | Maximum: 6 W |
| Material | Plastic |
| IR Range | Up to 130 ft (40 m) |
| Communication | Up the coax, Protocol: HIKVISION-C |
| Dimensions | Ø 5.35" × 4.01" (Ø 136 mm × 101.9 mm) |
| Weight | Approximately 1.76 lbs (800 g) |

Accessories

| | | | |
|---|---|---|---|
|  |  |  |  |
| CPM + PC130 Ceiling Pendant Mount and 130 mm Pendant Cap | WML+ PC130 Wall Mount Long and 130 mm Pendant Cap | PM Pole Mount Adaptor | RCM-3 Recessed Ceiling Mount |

Dimensions

