

DS-3E05xx-E Series Unmanaged Gigabit Switch



DS-3E0508-E



DS-3E0516-E



DS-3E0524-E

The DS-3E05xx-E is a 10/100/1000 Mbps unmanaged switch that requires no configuration and contains up to 24 Gigabit ports. It is ideal for managing simple installations that have a large volume of video traffic from high-megapixel IP cameras.

This series consists of basic standalone switches. Gigabit capability on all ports allows for multiple POE field switches to be connected on one DS-3E05xx-E Series core switch, which saves space and reduces the need to install additional devices.


- 10/100/1000 Mbps Auto-Negotiation RJ45 Ports
- Compliant with IEEE802.3, IEEE802.3u, and IEEE802.3ab Ethernet Standard
- IEEE802.3x Full-Duplex Flow Control, and Backpressure Half-Duplex Flow Control
- Plug-and-Play without Configuration
- LED Status Indicators
- Loop Detection and Prevention
- Auto MDI/MDIX Ports (DS-3E0516-E and DS-3E0524-E)
- Up to 4 kV Lightning Immunity for each Port

Available models: DS-3E0508-E, DS-3E0516-E, DS-3E0524-E

Specifications


	DS-3E0508-E	DS-3E0516-E	DS-3E0524-E
General			
Ports	8 x 10/100/1000Mbps auto-negotiation RJ45 ports	16 x 10/100/1000Mbps auto-negotiation RJ45 ports	24 x 10/100/1000Mbps auto-negotiation RJ45 ports
Network Standards	IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE 802.3x		
Transmission Speed	Ethernet: 10 Mbps (Half Duplex)/20 Mbps (full-duplex); Fast Ethernet: 100 Mbps (half-duplex)/200 Mbps (full-duplex); Gigabit Ethernet: 2000 Mbps (full-duplex)		
Transmission Medium	Ethernet: CAT3 or better UTP/STP cable; Fast Ethernet: CAT5 or better UTP/STP cable; Gigabit Ethernet: CAT5E or CAT6 UTP/STP cable (recommended)		
LED Indicator	1 x power LED; 8 x Link / Act LED	1 x power LED; 16 x Link / Act LED	1 x power LED; 24 x Link / Act LED
Dimensions (L x W x H)	7.32" x 4.20" x 1.31" (186 mm x 106.7 mm x 33.3 mm)	17.32" x 7.04" x 1.73" (440 mm x 178.8 mm x 44 mm)	
Mounting	Desk or Wall		1U height for desk or rack
Store-and-Forward	Supported		
MAC Address Table	4 k	8 k	
MAC Address Learning	Automatic learning/aging		
Package Filtering/Forwarding Rate	Ethernet: 14881 pps one port; Fast Ethernet: 148810 pps one port; Gigabit Ethernet: 1488100 pps one port		
Backplane Bandwidth	16 Gbps	32 Gbps	48 Gbps
Power Supply	Input: 100 to 240 VAC, 50 / 60 Hz, 0.3 A Output: 9 VDC, 1 A	Input: 100 to 240 VAC, 50 / 60 Hz	
Power Consumption	≤ 5.5 W	≤ 12 W	≤ 18 W
Operating Temperature	32° F to 104° F (0° C to 40° C)		
Operating Humidity	10 to 90% RH, non-condensing		
Storage Temperature	-40° F to 70° F (-40° C to 158° C)		
Storage Humidity	5 to 90% RH, non-condensing		
Port Type			
Port Loopguard	Supported		
Uplink Port	Port 8	Port 15 and 16	Port 23 and 24
Lightning-Proof Ranking			
RJ45 Port	4 kV	4 kV	
Power Source	2 kV	4 kV	

Front Panel




DS-3E0508-E

- | | |
|----|------------------------|
| 1. | Power LED Indicator |
| 2. | Link/Act LED Indicator |



DS-3E0516-E


- | | |
|----|------------------------|
| 1. | Power LED Indicator |
| 2. | Link/Act LED Indicator |
| 3. | RJ45 Port |



DS-3E0524-E


- | | |
|----|------------------------|
| 1. | Power LED Indicator |
| 2. | Link/Act LED Indicator |
| 3. | RJ45 Port |

Rear Panel



DS-3E0508-E

- | |
|---------------|
| 1. RJ45 Port |
| 2. Power Jack |



DS-3E0516-E and DS-3E0524-E

- | |
|-----------------------|
| 1. Grounding Terminal |
| 2. Power Jack |