



TELGUARD

EXDL-0

LTE, 3G/4G AND
CDMA NETWORKS

L T E M U L T I B A N D
N O G R O U N D P L A N E
O M N I D I R E C T I O N A L A N T E N N A



PRODUCT FEATURES

- Mechanically robust for both Indoor/Outdoor applications
- Self-contained design requiring no ground plane
- Applicable for both 3G and 4G application
- Domestic LTE 700 band and Global LTE 2600 band
- WiMAX 2300/2500/2600 bands

MODEL NUMBER

EXDL-0

INCLUDES

- Antenna with integral radial ground plane connector
- Mounting Bracket
- TNC Adapter

Cables not included.

For TG-1 Express use CTXL-12.

For TG-1B, TG-4, and TG-7 series, use ACD-12/35/50/100.

TECHNICAL DATA

| | |
|-----------------|--|
| Frequency Range | 698 - 960 MHz, 1710 - 2700 MHz |
| VSWR | |
| 698-806 MHz | <2.5: 1.0 |
| 806-960 MHz | <2.0: 1.0 |
| 1710-2700 MHz | <2.0: 1.0 |
| Peak Gain | |
| 698-960 MHz | 0 dBi |
| 1710-1990 MHz | 1.7dBi |
| 2100-2700 MHz | 2.9dBi |
| Polarization | Vertical |
| Pattern | Omnidirectional |
| Input Impedance | 50Ω |
| Maximum Power | 100 W |
| Cable & Mount | Included |
| Radome Material | High Heat ABS |
| Dimensions | 3.45" H x 1.45" dia. (8.76 cm x 3.68 cm) |