



**MODEL:HDO-58150TVI**

**Wireless Outdoor HD-TVI 1080p Video Tx & Rx kit,  
Range 2'500' - HDO-58150TVI**

INTRODUCING an economical wireless video solution for 720p and 1080p Hikvision Turbo HD TVI format security cameras. Perfect for applications ranging up to 2,500 Feet including: parking lots, driveways, gas stations, farming & livestock monitoring, storage facility, residential perimeter surveillance and more.



**Best Wireless Solution for TURBO HD-TVI cameras**

- Wireless Outdoor Point-to-Point TVI video solution **up to 2,500 Feet**
- Ready to install kit, No computer or programming software required
- Auto-Select 720p and 1080p TVI camera video resolution @ 30fps
- AES 128bit encryption for secure High Definition Video
- Embedded 12VDC 1000mA power output port for convenient camera power connection
- Rugged protective enclosures for extreme outdoor environments
- Economical solution to replace analog 960H wireless cameras
- Best solution for wireless AHD format cameras in parking lots, driveways, gated or private entrances, shopping mall, storage facility and applications where you can't pull cable.

## MODEL:HDO-58150TVI

## Wireless Outdoor HD-TVI 1080p Video Tx & Rx kit, Range 2'500' - HDO-58150TVI

### HDO-58150TVI Specifications

Operating Frequency:	5.185GHz - 5.825GHz
Modulation:	OFDM
Security Format:	AES 128 Bit Encryption
Resolution:	Auto-Select 720p ( 1280 x 720 ) / 1080p ( 1920 x 1080 )
Frame Rate:	maximum 30fps
Video Format:	720p / 1080p Hikvision Turbo HD-TVI cameras
Range & Elevation (Line of Sight):	2,500 feet @ Minimum 15 Feet Elevation
Antenna E Plane Beam:	30 Degrees
Video Connector:	Turbo HD-TVI BNC-Female
Video Impedance & Level:	75 Ohms @ 1 Volt P-P
Power Supplies Included:	2x 12VDC UL-Listed Power Supplies
Tx & Rx Power Connector:	2.1mm Barrel - Input & Output
Antenna Power Connector:	RJ-45 PoE System
Tx & Rx Operating Voltage:	12 Volts DC Input
Tx & Rx Current Consumption:	Tx 900mA / Rx 750mA
Tx & Rx Construction	Video Enclosure - IP-67 Rated All-Weather Design
Antenna Construction:	IP-53 Rated All-Weather Design
Dimensions:	Video = 7" x 7" x 4" (178mm x 178mm x 102mm) Each
Antenna Dimensions:	7.8 IN x 5.15 IN / (200mm x 131mm) Each
Weight:	14.2lbs / 6.44kg - Shipping
Antenna Mounting Bracket:	Universal ABS Plastic - Wall or Pole Mount
Operating Temperature Range:	-40°F to +170°F (-40°C to 77°C)
Note:	Camera Power Output = 12VDC @ Max 1000mA
Includes:	Transmitter & Receiver, 2x Antennas, Universal Mounting Brackets, 2x Power Supplies, One Year Limited Warranty & 100% Performance Guarantee
FCC / IC Approved:	Yes



[www.VideoTransmitters.com](http://www.VideoTransmitters.com)

Tel: 905.336.9665 Fax: 905.336.9662

©2016 1156488 Ontario Inc.