

PD4UL

UL Listed Power Distribution Module

Description

Altronix PD4UL UL Listed Sub-Assembly power distribution module is designed to convert a single AC or DC input into four (4) individually fuse protected outputs.



PD4UL

Specifications

Input

Voltage Range 12VDC or 24VDC, up to 10A or
24VAC or 28VAC, up to 12A.

Outputs

Four (4) fuse protected outputs.
2.5A per output max.
Total output current should not exceed max current rating of
power supply employed.
Fuses are rated @ 3.5A/250V.

Indicators (LED)

DC Output Power LED.

Agency Listings

UL:

Access Control UL294
Burglar Alarm UL603
Fire Alarm UL1481

cUL:

General Signaling Equipment Evaluated to
CSA Standard C22.2 No.205-M1983.
Power Supplies for Burglar Alarm Systems
ULC-5318-96.

Physical and Environmental

Dimensions (L x W x H)

5.25" x 3.25" x 1" (133.4mm x 82.6mm x 25.4mm).

Product Weight 0.15 lbs. (0.07 kg).

Shipping Weight 0.25 lbs. (0.11 kg).

Temperature

Operating 0°C to 49°C (32°F to 120°F).

Storage -20°C to 70°C (-4°F to 158°F).

Relative Humidity 85% +/-5%.

PD4UL

UL Listed Power Distribution Module

Board Dimensions (L x W x H) and Drawing

5.25" x 3.25" x 1" (133.4mm x 82.6mm x 25.4mm)

