

Uniden®

PRO·SERIES

Professional Video Security XVR System • Pro404X2



ONVIF



8.23"

1.91"

11.81"




BNC

1080p
Full HD

4
BNC Channels

4
IP Channels

2TB
Hard Drive



Manual Input Switch



Control remotely from your smartphone or tablet.

Technology you trust for the highest quality security.

uniden.com

Camera

Model No.: 2MED-3.6-BNC
 Sensor: 1/2.9" SONY 2MP CMOS
 Effective Pixels: 1920 (H) x 1080 (V)
 Video Frame Rate: 1080p@25/30fps
 Resolution: 1280H (CVBS output)
 Min. Illumination: 0 Lux (IR ON)
 Sync System: Internal
 Lens: Fixed 3.6mm M12 Lens, standard ICR module
 Electronic Shutter: Auto / Manual (X30-1/50000) / FLK
 S/N Rate: ≥ 50db (AGC OFF)
 Video Output: 1.0Vp-p complex video output, 75Ω
 Video Standard: PAL / NTSC adjustable

OSD Menu

White Balance: ATW/AWC-SET/INDOOR/OUTDOOR/MANUAL/AWB
 NR: 2DNR / 3DNR, OFF
 Image Adjustable: Brightness, Sharpness, AGC
 DWDR: AUTO / ON / OFF
 BLC: BLC / HLC / OFF
 AGC: 0-15
 Day & Night: B/W, COLOR, AUTO, EXT
 Privacy Mask: OFF / ON (4 zones)
 Motion Detection: OFF / ON (4 zones)
 Mirror: Horizontal / Vertical / Rotation
 Sens-up: OFF / ON (X30, X25, X20, X15, X10, X8, X6, X4, X2)
 Lens Shading Compensation: OFF / ON
 DPC: Auto, B/W

Defog: OFF / Auto
 OSD Menu: English, Chinese, 12 languages
 Four-in-One Output: AHD 1080p, TVI 1080p, CVI 1080p, CVBS 1280H (optional)

Camera General

IR Distance: 100' Night Vision (16 x SMT LEDs)
 Protection Grade: IP65
 Communication: Support UTC control
 Power Jack: 2.1mm Power Jack for 12VDC input
 Power: 12VDC± 10%
 Power Consumption(max): <3.9w (IR LED+ board:0.96w)
 Operating Temperature: -4°F-131°F
 Operating Humidity: 0%-90%
 Dimensions (in.): 4.72(L) * 4.72(W) * 3.74(H)
 Weight (oz): 14

XVR Video

Five-in-One Input: 1080p AHD, TVI, CVI, IP, 1280H Analog
 Video Compression: H.264
 Video Resolution: 4MP / 3MP / 1080p / 960p / 720p / D1 / 4CIF / DCIF / 2CIF / CIF / QCIF
 Video Input: 4CH*2MP (BNC) @4main Play, 2CH*4MP (BNC1, BNC4) @2main Play, 4CH*2MP (BNC) +4CH*2MP(IPC) @4Sub-Play /1main Play, 2CH*4MP (BNC1, BNC4) +2CH*4MP(IPC) @2Sub-Play/1main Play
 Video Output: VGA / HDMI
 Sync Output: 1920x1080p@60Hz,

1920x1080p@60Hz, 1440x900p@60Hz, 1366x768p@60Hz, 1280x1024p@60Hz, 1024x768p@60Hz, 800x600p@60Hz
 Bit Rate: self-define 16-8000Kbps
 Image Display: 1/4/6/8/9
 Snapshot: Support (JPEG)
 Motion Detection: 396(22*18) surveyed area can be set in every screen and multi-level sensitivity adjustable
 Video Standard: PAL; NTSC

Audio

Audio Encoding G.711u
 Audio Input: 4CH, RCA port
 Audio Output: 1CH, RCA port

Video Recording And Playback

Video Frame Rate:
 •4CH mode 1080p@15fps, 720p@25fps (PAL)/30fps (NTSC) real-time, analog/IPC@25fps (PAL)/30fps (NTSC) real-time
 •2CH mode 4MP@15fps, 3MP@10fps, 1080p@25fps (PAL)/30fps (NTSC) real-time, 720p@25fps (PAL)/30fps (NTSC) real-time, analog/IPC@25fps (PAL)/30fps (NTSC) real-time
 Record Mode: Manual / Timing / MD / Alarm exception / MD or alarm / MD and alarm
 Playback Synchronic: Analog 4CH/mixed 1CH sync playback (main stream), 2CH/4CH sync playback (sub stream)
 Search Method: Time, Calendar, Event, Channel
 Video Playback: Start, Stop, Fast play, Slow play, Frame

play, Snapshot, Full screen, Roller amplification time ball precise playback

Storage Backup

Interface: 1 SATA
 HDD Capacity: Single largest 6TB
 Backup Location: Local HDD, network
 Backup Method: Network backup, USB storage device

Function

Network Protocol: TCP/IP, HTTP, DDNS, SMTP(SSL), DHCP, PPPOE, UPNP, NTP, P2P, ONVIF
 Interface Protocol: ONVIF, RTSP
 Mobile Surveillance: Apple, Android
 Browser: IE, Chrome, Firefox, Safari
 Intelligent Detection: Motion detection, video loss, video tampering

External Interface

Video Input: 4CH BNC port (1.0Vp-p,75Ω)
 Network Interface: 1 RJ45 10M/100M self-adaptive ethernet port
 Alarm Input: 4CH
 RS485 Interface: 1 RS485 port
 USB Port: 2 (USB2.0)

XVR General

Operating Temperature: -4°F-131°F
 Operating Humidity: 10%-90%
 Power Supply: <10W
 Power Consumption: 12VDC/3A
 Dimensions (in.): 11.81(L) * 8.23(W) * 1.91(H)



FREE Uniden Pro Wired App

Full Mobile remote control and setup from iPhone®, iPad®, iPod touch® and Android™ devices. Receive alerts via Email or Notification.

SYSTEM REQUIREMENTS: Router with Internet access and available Ethernet Port, iPhone®, iPad®, iPod touch® or Android™ device.

PACKAGE INCLUDES: (1) 4 Channel XVR, (4) Outdoor Cameras, (4) 100' BNC Video Cables, (1) 6ft Ethernet Cable, (1) 6ft HDMI Cable, (1) 12V Power Adapter for Cameras and XVR, (1) 5-Way Power Splitter for Cameras, (1) USB Mouse, (4) Camera Mounting Hardware, (1) Quick Start Guide

©2017 Uniden America Corp., Irving TX. All rights reserved. Photography and illustrations may differ slightly from actual product. iPad®, iPhone® and iPod touch® are registered trademarks of Apple Inc. Android is a trademark of Google Inc. Amazon, Kindle, Fire and all related logos are trademarks of Amazon.com, Inc. or its affiliates. May contain additional foreign articles. Custom manufactured in China.

Proposition 65 Warning (California): This product contains a chemical known to The State of California to cause cancer, birth defect or other reproductive harm.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

UPC: 0 5063340746 2