



ARLO PRO 2 VIDEO SYSTEM



TELGUARD



Up to five Arlo cameras can be added to a HomeControl Flex system for no monthly service fee.

RESIDENTIAL PRODUCT SYSTEM FEATURES

- Low maintenance and user-friendly.
- Can be used as a stand-alone video system, and can easily integrate with HomeControl Flex™, Telguard's interactive solution.
- USB Access for local storage of recorded video clips.
- System requires both Arlo Pro 2 Wire-free HD Camera and Arlo Pro Base Station (each sold separately).

ARLO PRO 2 CAMERA FEATURES

- 100% Wire-free, eliminating power cords and wiring hassles.
- Delivers 1080p HD live video - more detail than ever before.
- Advanced sound and motion detection, and 2-way audio.
- IP65 certified weather-resistant, allowing both indoor & outdoor use.
- Night vision of up to 25 feet.
- Includes one rechargeable battery (Arlo Solar Panel also available).
- Advanced features: Activity Zones, 3-second look-back & 24/7 CVR.

Comprised of the flexible, award-winning and easy to install Arlo Pro 2 Wire-free HD Camera and the Arlo Pro Base Station, the Arlo Pro 2 Video System is supported by Telguard's industry renowned customer support team.

Flexible Video Solution

The Arlo Pro Video 2 System gives Dealers a way to offer their customers the highest quality residential video system with the shortest installation time of 10 minutes or less. Low maintenance and user-friendly, the Arlo Pro 2 Video System gives users the ability to make adjustments themselves, including relocating the camera and replacing or recharging batteries.

HomeControl Flex Integration

Integrating the Arlo Pro 2 Video System with Telguard's HomeControl Flex interactive solution allows you to integrate the Arlo Pro 2 Video System with your customers' professionally monitored security systems. With HomeControl Flex and an Arlo Pro 2 Wire-free HD Camera, enable remote viewing of event-triggered clips, images and live video from anywhere, on a smartphone, computer or tablet.

Telguard Support

Telguard offers all their Dealers and Installers industry renowned customer support, ensuring all installations and activations are quick and easy. As the thought leader in the industry, Telguard has proven their drive to embrace the integration of consumer lifestyle products with professionally installed security systems.



ARLO PRO 2 VIDEO SYSTEM



TELGUARD

Arlo Pro 2 Camera Specifications

- **Dimensions:** 3.1 x 1.9 x 2.8 in (79.3 x 48.6 x 70.5 mm).
- **Weight:** 4.8 oz (136g).
- **Battery Life:** Varies based on setting, usage and temperature.
- **Resolution:** Up to 1080p HD.
- **Format:** H.264.
- **Field of View:** 130°.
- **Night Vision:** 850 nm LEDs. Illuminates up to 25 feet. IR Cut-Off Filter.
- **Imaging Sensor:** Full Color CMOS. Auto-Adaptive White/Black Balance and Exposure.
- **Requirements:** Arlo Pro Base Station and High-Speed Internet Connection.

Wireless

- **Frequency:** 2.4GHz, 802.11n.
- **Range:** 300+ Feet Line of Sight.

Weather-Resistant

- **Camera Operating Temperature:** -4 to 113° F (-20 to 45° C).
- **Weather-Resistant:** IP65 Certified.

Arlo Pro Base Station Specifications

- **Requirements:**
 - High-Speed Internet Connection Minimum 1 Mbps Upstream Recommended
 - Available Port on Customer's Router.
- **Dimensions:** 2.3 x 6.9 x 5.0 in (58.6 x 174.5 x 126.5 mm).
- **Weight:** 11.1 oz (316g).



ARLO



ARLO PRO



ARLO PRO 2

	ARLO	ARLO PRO	ARLO PRO 2
100% Wire-free	✓	✓	✓
Weather-resistant (IP65)	✓	✓	✓
Motion Detection	Great	Best	Best
Motion Alerts	✓	✓	✓
Sound Detection	✗	✓	✓
Security System Alerts with HomeControl Flex	✓	✓	✓
HD Quality	720p	720p	1080p
Night Vision	✓	✓	✓
Digital Pan and Zoom	✓	✓	✓
Local Video Clip Backup (if connected to an Arlo Pro Base station)	✓	✓	✓
Smart Siren (if connected to an Arlo Pro Base station)	✓	✓	✓
Wide Viewing Angle	110°	110°	130°
2-Way Audio	✗	✓	✓
Rechargeable Battery	✗	✓	✓
AC Power Option	✗	✓	✓
Solar Power Option	✗	✓	✓
Free Cloud Storage (7 days for Free)	✓	✓	✓
Advanced Features: 3-sec. Look Back, Activity Zones, 24/7 CVR (when plugged in and used indoors)	✗	✗	✓