



## **RC8030 MPEG4 PAN/TILT IP CAMERA (WIRELESS) TECHNICAL SPECIFICATIONS ///**

Our plug-and-play **Wireless** RC8030 MPEG4, Pan-and-Tilt, Indoor Network Surveillance IP Camera connects wirelessly to your Gateway. Connect up to 8 of these remotely accessible cameras to view live real-time video of your home or business via your web-enabled mobile phone or pc, from anywhere, anytime.

### **TECHNICAL SPECIFICATIONS ///**

- CIF Resolution (320 x 240) at 30 Frames-per-second
- Supports MPEG-4 and M-JPEG Dual Video Streaming
- Supports Mobile Phone Live Video

Image Sensor:	CMOS, 1/4" VGA Resolution
Lens:	F2.0 Fixed Focus
Effective Range:	50cm to Infinity
Resolution Support:	320 x 240, 160 x 120
Typical Range Indoors:	164 Feet
Pan Range:	126°(Left 63° ~ Right 63°) + 57° View Angle
Tilt Range:	64°(Up 28° ~ Down 36°) + 57° View Angle
Digital Zoom	
Min. Illumination:	1.0 Lux
Camera Size:	3.1"D x 3.8"W x 5.7"H (78mm x 96mm x 146mm)