

IQ Panel 4

Moving the Goalposts ... again

H70° L56°	12:55 PM 11/11/21	ACTIVE ALL		
SY	stem S armed		0	
	•1.0	♥ & +		

IQ Panel 4 PowerG + 319.5MHz

IQ Panel 4 PowerG + 345MHz

IQ Panel 4 PowerG + 433MHz



Easiest Installation Ever SmartMount system, all internal antennas, on-screen Installation Wizard

QuadSound Audio Streaming Bluetooth Audio from your Smart Phone using four 4 watt speakers



Best Built-in Camera 8MP 120° wide angle camera w/ FlexTilt. Peek-in, Disarm Photos, Alarm Videos



Better All-In-One Range LTE and WiFi Dual-Path, Dual SRF featuring PowerG, Z-Wave 700 Series, Bluetooth 4.2

ž=

Best Differentiating Features Bluetooth Touchless Disarming, Live View, Live Answer, Built-in Glass Break



Best Integrations Best in class Residential Comm

Best in class Residential, Commercial, MDU, Builder, Wellness support

Johnson Controls

IQ Panel 4

SPECIFICATIONS			
Items	Parameters	IQ Panel 4	
LCD Display	Size	7 inch LCD	
	Resolution	1280 x 800 pixels	
	Brightness	300 cd/m2	
	RGB Color	24bit, 16.9 Million Colors	
Touchscreen	Туре	Capacitive glass multi-touch	
User Codes	Up to 242	Role-based (Dealer, Installer, Master, User, Guest, Duress)	
Network	WiFi	WiFi 802.11 a/b/g/n/ac dual band 2.4/5GHz - including built-in access point capability	
	Cellular	LTE Category 4 (Bands 2/25, 4/66, 5, 7, 12/17, 13, 14 Non-FirstNet, 26)	
Z-Wave Plus (700)	Up to 137 Devices	137 total (Up to 80 lights, up to 20 locks, up to 10 thermostats, up to 6 garage doors, up to 21 misc.)	
PowerG	Up to 128 Devices	915 MHz Long Range Secure Encrypted 2-Way Wireless	
Security RF	Up to 128 Devices	Depending on the model: Either S-Line Encrypted 319.5 MHz, 345 MHz, or 433 MHz	
Bluetooth	Disarm & Audio Streaming	Bluetooth Low Energy (BLE) 4.2	
Flash Memory	Internal Storage	16GB NAND Flash	
LED Indicator	Status LED	Triple full color RGB LED	
Speaker/Siren	4W x 4	QuadSound 4x front-facing 4W speakers and 85-decibel siren	
Camera	Front Camera	8MP Wide-Angle, 120° Field-of-View, Fixed-Focus Camera, with Flex-Tilt Adjustment	
Microphone	MEMS x3	3 MEMS (Micro-Electro-Mechanical System) Microphones with Echo Cancellation	
Tamper	Tamper Switch	Dual panel and wall tamper with spring release and Smash and Grab reporting	
Battery	Туре 18650	Rechargeable Lithium Ion 3000mAh Rated for over 24 hours	
Buttons	Hard Button	Single wake/sleep button, all user controls through touch interface	
Mechanical	Dimensions	6.1"H x 7.5"W x 1"D(155mm x 191mm x 26mm)	
Power Supply	DC	7v DC 1000mA CC, Input 100-240VAC 50/60Hz Adpater evaluated at 120vAC for UL/cUL	
Mount	Back Plate	SmartMount for wall mounting included. SmartMount table stand or SmartMount IQ Base Table Stand with built-in Subwoofer sold separately	
Certifications	FCC	FCC: 2AAJXQS-IQPANEL4 (may contain additional modules with separate FCC IDs)	
	IC	IC: 11205A-QSIQPANEL4	
	UL	UL-985, UL-1023, UL2610, ULC-S545, ULC-S304	
Temperature	Operational	0°C to 49°C, 32°F to 120.2°F, up to 93% relative humidity, indoor, dry ordinary locations use only	
	Storage	-20°C to 50°C, -4°F to 122°F	
Operating System	Android 9	Security & Home Automation Touch and Swipe Interface	
Processor	8 core	Qualcomm Snapdragon 8 core SOM (System on a Module) with 16GB of NAND Flash	

